NSN 5306-00-949-5483

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-949-5483 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 6.031 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** 5.562 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 5.874 inches first hole Material: Stainless steel **Material Specification:** Qq-s-770 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-b-6812 military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5306-00-949-5483

Machine Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.