

View Online at <https://aerobasegroup.com/nsn/5306-00-950-3307>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.480 inches and 0.500 inches

**Fastener Length:**

Between 1.258 inches and 1.310 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**Shoulder Diameter:**

0.245 inches first shoulder and 0.247 inches first shoulder

**Shoulder Length:**

0.700 inches first shoulder and 0.720 inches first shoulder

**Thread Diameter:**

0.190 inches

**Nonstandard Thread Pitch Diameter:**

+0.1644/+0.1667 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

80.0 rockwell b

**Shoulder Shape:**

Round first shoulder

**Material:**

Stainless steel

**Material Specification:**

850t12a, fscm 07482 mfr ref single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0