NSN 5306-00-951-1104

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-951-1104

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.062 inches |
| Fastener Length: |
| 1.812 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.547 inches and 0.578 inches |
| Width Between Flats: |
| Between 1.053 inches and 1.064 inches |
| Hole Diameter: |
| 0.062 inches |
| Thread Diameter: |
| 0.750 inches |
| Grip Length: |
| 0.750 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 10 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 |
| Material Specification: |
| Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military |
| specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material |
| response or ams 6300 assn standard 6th material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification all treatment responses |

Unc

Thread Series Designator:

NSN 5306-00-951-1104

Machine Bolt - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |

Mil-std (military Standard):

Mil-s-5626 spec.

Shelf Life: