NSN 5306-00-951-1264

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-951-1264
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.242 inches and 0.355 inches
Fastener Length:
1.400 inches
Head Style:
Hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.045 inches and 1.158 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon flats
Surface Finish:
63.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response

Cadmium

Surface Treatment:

NSN 5306-00-951-1264

Machine Bolt - Page 2 of 2



Surface Treatment	Specification:
-------------------	----------------

Qq-p-416 tu 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.