

View Online at <https://aerobasegroup.com/nsn/5306-00-952-2636>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.663 inches and 0.713 inches

Fastener Length:

Between 1.235 inches and 1.265 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.615 inches and 0.625 inches

Head Height:

0.343 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.375 inches and 0.378 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.021 inches first hole and 1.041 inches first hole

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 3140 or steel comp 3135

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas146 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0