

View Online at <https://aerobasegroup.com/nsn/5306-00-952-6757>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.826 inches

Fastener Length:

4.451 inches

Head Style:

Double hexagon w/hole

Head Height:

0.557 inches

Width Between Flats:

Between 0.619 inches and 0.628 inches

Extended Washer Diameter:

0.933 inches

Extended Washer Thickness:

0.133 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Thread Diameter:

0.562 inches

Grip Length:

3.625 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Product Name:

Navy special project

Material:

Steel comp e4340 or steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6098 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response or mil-s-5626 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas629 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.