

View Online at <https://aerobasegroup.com/nsn/5306-00-954-0969>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.609 inches and 0.688 inches

Fastener Length:

Between 1.937 inches and 1.984 inches

Head Style:

Hexagon

Head Height:

Between 0.265 inches and 0.297 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Grip Diameter:

Between 0.4986 inches and 0.4991 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 1.296 inches and 1.328 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Surface Finish:

63.0 microinches grip

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 8630 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0