NSN 5306-00-955-8690

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-955-8690

Thread Class.
Thread Class:
3a Through Birnerian
Thread Direction:
Right-hand Thread Longton
Thread Length:
0.852 inches
Fastener Length:
4.372 inches
Head Style:
Double hexagon w/hole
Head Height:
0.557 inches
Width Between Flats:
Between 0.616 inches and 0.627 inches
Extended Washer Diameter:
Between 0.928 inches and 0.938 inches
Extended Washer Thickness:
0.133 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Thread Diameter:
0.562 inches
Grip Length:
3.500 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-00-955-8690

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0