NSN 5306-00-957-1495

Machine Bolt - Page 1 of 2

Between 0.563 inches and 0.625 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

0.625 inches

За



View Online at https://aerobasegroup.com/nsn/5306-00-957-1495

Head Style:
Double hexagon w/hole
Head Height:
0.260 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
0.375 inches
Extended Washer Thickness:
Between 0.040 inches and 0.050 inches
Hole Diameter:
0.047 inches
Thread Diameter:
0.190 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Finished head Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Thready Qty Per Inch (tpi): 32 Hardness Rating:
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style:
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish:
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 8740
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 8740 Material Specification:
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment:
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response
Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment:

NSN 5306-00-957-1495

Machine Bolt - Page 2 of 2



Surface Treatment S	Specification:
---------------------	----------------

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0