

View Online at <https://aerobasegroup.com/nsn/5306-00-957-2294>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.094 inches

**Fastener Length:**

3.406 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.390 inches and 0.422 inches

**Width Between Flats:**

Between 1.053 inches and 1.066 inches

**Grip Diameter:**

Between 0.7481 inches and 0.7488 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

2.312 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.187 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-b-6812 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.