NSN 5306-00-957-7050

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-957-7050 **Thread Direction:** Right-hand Thread Length: Between 0.647 inches and 0.662 inches **Fastener Length:** Between 0.802 inches and 0.822 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.445 inches and 0.455 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Shoulder Diameter:** 0.345 inches first shoulder and 0.355 inches first shoulder **Shoulder Length:** 0.155 inches first shoulder and 0.160 inches first shoulder **Thread Diameter:** 0.190 inches **Nonstandard Thread Pitch Diameter:** +0.1644/+0.1667 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** Minor fia of thd 0.1487 in max Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-00-957-7050 Shoulder Bolt - Page 2 of 2



Fiig:

A003b0