## NSN 5306-00-958-5420

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-958-5420

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

0.852 inches

#### Fastener Length:

2.372 inches

#### Head Style:

Double hexagon w/hole

**Head Height:** 

0.557 inches

Width Between Flats:

Between 0.616 inches and 0.627 inches

#### **Extended Washer Diameter:**

Between 0.928 inches and 0.938 inches

#### **Extended Washer Thickness:**

0.133 inches

**Grip Diameter:** 

Between 0.5605 inches and 0.5615 inches

#### Single Shear Strength:

108000 pounds per square inch

## Thread Diameter:

0.562 inches

#### Grip Length:

1.500 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

#### Hardness Rating:

 $39.0\ rockwell\ c$   $% 100\ rockwell\ c$  and  $43.0\ rockwell\ c$ 

## Material:

Steel comp 8740 or steel comp e4340 or steel comp 4340 or steel comp 6150 or steel comp 4140

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 ty2, class 3 federal specification single treatment response

## Thread Series Designator:

Unf

#### Shelf Life:

N/a

# NSN 5306-00-958-5420

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

