## NSN 5306-00-964-0378

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-964-0378 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.736 inches and 0.750 inches **Locking Feature:** Distortions bearing surface of head **End Application:** Spec item **Thread Diameter:** 0.500 inches **Grip Length:** 0.188 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 150000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 38.0 rockwell c Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232, ty z, cl 2 military specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5306-00-964-0378

Machine Bolt - Page 2 of 2



Ini	1 (	Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-p-16232 spec.