NSN 5306-00-971-7199

Machine Bolt - Page 1 of 2

Between 0.794 inches and 0.814 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-00-971-7199

| Between 0.865 inches and 0.885 inches |
|---|
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.320 inches and 0.340 inches |
| Width Between Flats: |
| Between 0.304 inches and 0.313 inches |
| Extended Washer Diameter: |
| Between 0.428 inches and 0.448 inches |
| Extended Washer Thickness: |
| Between 0.060 inches and 0.070 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.250 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| C8 |
| Hardness Rating: |
| 30.0 rockwell c and 38.0 rockwell c |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Surface Finish: |
| 63.0 microinches bearing surface of head |
| Material: |
| Steel comp 601 |
| Material Specification: |
| Ams 6304 assn standard single material response |
| Surface Treatment: |
| Nickel and cadmium |
| |
| |

NSN 5306-00-971-7199

Machine Bolt - Page 2 of 2



| Surface | Treatment | Specifi | cation: |
|---------|------------------|---------|---------|
| Juliace | I I Callillelli | Specili | calion. |

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0