Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-973-1721

| Tread Class:<br>2a<br>Tread Direction:<br>Right-hand<br>Tread Longth:<br>0.875 inches<br>Fastome Longth:<br>1.825 inches<br>Fastome Longth:<br>1.825 inches<br>Head Style:<br>Head Style:<br>Head Style:<br>Head Height:<br>0.150 inches<br>With Between Flats:<br>0.323 inches<br>First Diameter From Head:<br>0.323 inches<br>Distance From Largest Bearing Surface Of Head To End Of First Diameter:<br>0.350 inches<br>Thread Diameter:<br>0.161 inches<br>Thread Diameter:<br>0.150 inches<br>Thread Diameter:<br>0.190 inches<br>Thread Style Plinch (tpi):<br>24<br>Externally Relieved Body Diameter Quantity:<br>1<br>Thread Series Designator:<br>Unc<br>Shelf Life:<br>Na<br>Dimiliarization:<br>Na<br>Fig:<br>A003b0   |   |
|--|---|
| Tread Direction:         Right-hand         Tread Length:         0.875 inches         Fastenr Length:         1.625 inches         Head Style:         Head Style:         Head Style:         1.625 inches         Head Style:         1.625 inches         Head Style:         1.623 inches         Vidth Between Flats:         0.150 inches         First Diameter From Head:         0.161 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.750 inches         Thread Diameter:         0.190 inches         Thread Val Per Inch (tpi):         24         Externally Relieved Body Diameter Quantity:         1         Ince         Sheft Life:         Iva         Iva      I   | Thread Class:   |
| Right-hand         Ivread Length:         0.875 inches         Fastener Length:         1.625 inches         Head Style:         Head Style:         Head Style:         Head Height:         0.150 inches         Vidth Between Flats:         0.323 inches         First Diameter From Head:         0.323 inches         First Diameter From Head:         0.161 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.750 inches         Thread Diameter:         0.190 inches         Thread Yup Per Inch (tpl):         24         Externally Relieved Body Diameter Quantity:         1         Thread Series Designator:         Inci         Na         Unit Of Measure:         -         -         Penillitarization:         Na   | 2a  |
| Tread Length:         0.875 inches         Fastener Length:         1.625 inches         Head Style:         Head Style:         Head Style:         Head Style:         O.100 inches         Width Between Flats:         0.132 inches         First Diameter From Head:         0.132 inches         Distance From Head:         0.161 inches         Distance From Head:         0.150 inches         Thread Diameter:         0.150 inches         Thread Diameter:         0.190 inches         Thread Quy Per Inch (tpi):         24         Externally Relieved Body Diameter Quantity:         1         Thread Steise Designator:         Inci         Na         Inci Measure:         Image:  | Thread Direction:   |
| 0.875 inches         Fastener Length:         1.625 inches         Head Style:         Head Style:         Hexagon         Head Height:         0.150 inches         Width Between Flats:         0.323 inches         First Diameter From Head:         0.161 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.750 inches         Thread Diameter:         0.190 inches         Thready Qty Per Inch (tpi):         24         Externally Relieved Body Diameter Quantity:         1         Inc         Sheff Life:         Na         Unic         Sheff Life:         Na         Dint Of Measure:         -         Fig:   | Right-hand  |
| Fastener Length:         1.625 inches         Head Style:         Hexagon         Head Height:         0.150 inches         With Between Flats:         0.323 inches         First Diameter From Head:         0.161 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.161 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.162 inches         Thread Diameter:         0.190 inches         Thread Plaimeter:         10 inches         Thread Style Planch (tpi):         24         Extensity Relieved Body Diameter Quantity:         1         Thread Series Designator:         Ince         Na         Int of Measure:            Pomilitarization:         No         Fig:  | Thread Length:  |
| <ul> <li>1.825 inches</li> <li>Head Style:</li> <li>Hexagon</li> <li>Head Height:</li> <li>0.150 inches</li> <li>Width Between Flats:</li> <li>0.323 inches</li> <li>First Diameter From Head:</li> <li>0.323 inches</li> <li>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</li> <li>0.750 inches</li> <li>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</li> <li>0.750 inches</li> <li>Thread Diameter:</li> <li>0.750 inches</li> <li>Thread Diameter:</li> <li>0.750 inches</li> <li>Thread Vary Per Inch (tpi):</li> <li>24</li> <li>Externally Relieved Body Diameter Quantity:</li> <li>1</li> <li>Thread Series Designator:</li> <li>Unc</li> <li>Shelf Life:</li> <li>N/a</li> <li>Unit Of Measure:</li> <li>-</li> <li>Demilitarization:</li> <li>No</li> <li>Fig:</li> </ul>   | 0.875 inches  |
| Head Style:HexagonHead Height:0.150 inchesWidth Between Flats:0.323 inchesFirst Diameter From Head:0.161 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesThread Diameter:0.190 inchesThread Y Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1Thread Series Designator:UncShelf Life:NaInit of Measure:Pomilitarization:NoFig:   | Fastener Length:  |
| HexagonHead Height:0.150 inchesWidth Between Flats:0.323 inchesFirst Diameter From Head:0.161 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1IncShelf Life:NaUnic Of Measure:Inic Of Measure:NaPinilitarization:NoFig:  | 1.625 inches  |
| Head Height:0.150 inchesWidth Between Flats:0.323 inchesFirst Diameter From Head:0.161 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1Thread Series Designator:UncShelf Life:N/aInt of Measure:Int of Measure:I | Head Style:   |
| 0.150 inchesWidth Between Flats:0.323 inchesFirst Diameter From Head:0.161 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1Thread Series Designator:UncShelf Life:N/aUnit Of Measure:-Denilitarization:NoFig:  | Hexagon   |
| Width Between Flats:0.323 inchesFirst Diameter From Head:0.161 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1InceShelf Life:NaUncDinc Of Measure:Demilitarization:NoFig:   | Head Height:  |
| 0.323 inches First Diameter From Head: 0.161 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 fread Series Designator: Unc Shelf Life: Na Unc Dinc Of Measure: Demiltarization: No Fig:  | 0.150 inches  |
| First Diameter From Head:         0.161 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.750 inches         Thread Diameter:         0.190 inches         Thready Qty Per Inch (tpi):         24         Externally Relieved Body Diameter Quantity:         1         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:   | Width Between Flats:  |
| 0.161 inches<br>Distance From Largest Bearing Surface Of Head To End Of First Diameter:<br>0.750 inches<br>Thread Diameter:<br>0.190 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Externally Relieved Body Diameter Quantity:<br>1<br>Thread Series Designator:<br>Unc<br>Shelf Life:<br>N/a<br>Dint Of Measure:<br><br>Demilitarization:<br>No  | 0.323 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:0.750 inchesThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:11Thread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:   | First Diameter From Head:   |
| 0.750 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:  | 0.161 inches  |
| Thread Diameter:         0.190 inches         Thready Qty Per Inch (tpi):         24         Externally Relieved Body Diameter Quantity:         1         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:  | Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.190 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Externally Relieved Body Diameter Quantity:<br>1<br>Thread Series Designator:<br>Unc<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>No   | 0.750 inches  |
| Thready Qty Per Inch (tpi):         24         Externally Relieved Body Diameter Quantity:         1         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:   | Thread Diameter:  |
| 24<br>Externally Relieved Body Diameter Quantity:<br>1<br>Thread Series Designator:<br>Unc<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>No  | 0.190 inches  |
| Externally Relieved Body Diameter Quantity:   1   1   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:   | Thready Qty Per Inch (tpi):   |
| 1   Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:   | 24  |
| Thread Series Designator:   Unc   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:   | Externally Relieved Body Diameter Quantity:                             |
| Unc<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>No   | 1   |
| Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:   | Thread Series Designator:   |
| N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>No<br>Fiig:  | Unc   |
| Unit Of Measure:<br><br>Demilitarization:<br>No<br>Fiig:   |   |
| <br>Demilitarization:<br>No<br>Fiig:   |   |
| Demilitarization:<br>No<br>Fiig:   | Unit Of Measure:  |
| No<br>Fiig:  |   |
| Fiig:  | Demilitarization:   |
|  |   |
| A003b0   |   |
|  | A003b0  |
|  |   |
|  |   |