

View Online at <https://aerobasegroup.com/nsn/5306-00-974-7501>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.531 inches

**Fastener Length:**

1.500 inches

**Head Style:**

Hexagon

**Head Height:**

0.312 inches

**Width Between Flats:**

0.687 inches

**First Diameter From Head:**

0.468 inches

**Second Diameter From Head:**

0.375 inches

**Third Diameter From Head:**

0.468 inches

**Fourth Diameter From Head:**

Between 0.284 inches and 0.294 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.593 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.663 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.812 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

0.968 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

100000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0