NSN 5306-00-974-7501

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-974-7501 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** 1.500 inches **Head Style:** Hexagon **Head Height:** 0.312 inches Width Between Flats: 0.687 inches **First Diameter From Head:** 0.468 inches **Second Diameter From Head:** 0.375 inches **Third Diameter From Head:** 0.468 inches **Fourth Diameter From Head:** Between 0.284 inches and 0.294 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.593 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.663 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.812 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.968 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 100000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 4 Material: Steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141

Thread Series Designator:

Unc

NSN 5306-00-974-7501

Externally Relieved Body Bolt - Page 2 of 2



She	lf	L	if	е	:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0