

View Online at <https://aerobasegroup.com/nsn/5306-00-980-2276>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.355 inches and 0.416 inches

Fastener Length:

Between 2.553 inches and 2.594 inches

Head Style:

Hexagon

Head Height:

Between 0.151 inches and 0.171 inches

Width Between Flats:

Between 0.490 inches and 0.502 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 2.178 inches and 2.198 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.