NSN 5306-00-982-7942

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-982-7942

View Online at https://aerobasegroup.com/nsn/5306-00-982-7942
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
2.500 inches
Head Style:
Hexagon
Head Height:
Between 0.195 inches and 0.211 inches
Width Between Flats:
Between 0.489 inches and 0.500 inches
Thread Diameter:
0.312 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Surface Finish:
63.0 microinches threads
Special Features:
Material document and classification reply 23, 66 reply 24, 66
Material:
Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel
comp 348 or steel comp 385
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

2 type and 10n etyle

Specification Or Standard:

Unc

NSN 5306-00-982-7942

Machine Bolt - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0