

View Online at <https://aerobasegroup.com/nsn/5306-00-987-9460>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

Between 2.297 inches and 2.327 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.296 inches and 0.328 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6234 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.802 inches and 1.822 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

24.0 rockwell c and 35.0 rockwell c

**Minimum Yield Strength:**

85000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.128 inches first hole and 2.140 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0