NSN 5306-00-990-1601

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-990-1601

| /iew Online at https://aerobasegroup.com/nsn/5306-00-990-1601 | |
|--|--------|
| Thread Class: | |
| Ba | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.632 inches | |
| Fastener Length: | |
| Between 3.617 inches and 3.647 inches | |
| lead Style: | |
| lexagon | |
| lead Height: | |
| Between 0.172 inches and 0.204 inches | |
| Vidth Between Flats: | |
| Between 0.492 inches and 0.501 inches | |
| Thread Diameter: | |
| 0.312 inches | |
| Grip Length: | |
| Between 2.985 inches and 3.015 inches | |
| Features Provided: | |
| Casehardened and finished head | |
| Fhready Qty Per Inch (tpi): | |
| 24 | |
| /in. Tensile Strength (psi): | |
| 40000 pounds per square inch | |
| Naterial: | |
| Stainless steel | |
| Naterial Specification: | |
| Ams 5733 assn standard single material response or ams 5735 assn standard single material response or ams 5737 assn standard s | single |
| naterial response | |
| Surface Treatment: | |
| Passivate | |
| Thread Series Designator: | |
| Jnf | |
| Shelf Life: | |
| N/a | |
| Jnit Of Measure: | |
| - | |
| Demilitarization: | |
| 10 | |
| iig: | |
| A003b0 | |