## NSN 5306-00-990-1644

Machine Bolt - Page 1 of 2



90-1644

| View Online at https://aerobasegroup.com/nsn/5306-00-990    |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.633 inches and 0.693 inches                       |
| Fastener Length:  |
| Between 1.898 inches and 1.928 inches                       |
| Head Style:   |
| Hexagon   |
| Head Height:  |
| Between 0.203 inches and 0.235 inches                       |
| Width Between Flats:  |
| Between 0.554 inches and 0.564 inches                       |
| Thread Diameter:  |
| 0.375 inches  |
| Grip Length:  |
| Between 1.235 inches and 1.265 inches                       |
| Features Provided:  |
| Finished head   |
| Thready Qty Per Inch (tpi):                                 |
| 24  |
| Min. Tensile Strength (psi):                                |
| 140000 pounds per square inch                               |
| Material:   |
| Iron alloy 660  |
| Material Specification:                                     |
| Ams 5732 assn standard single material response             |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:                            |
| Mil-s-5002 military specification single treatment response |
| Thread Series Designator:                                   |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| -   |

A003b0

## NSN 5306-00-990-1644

Machine Bolt - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5002 spec.

