

View Online at <https://aerobasegroup.com/nsn/5306-00-993-2714>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.342 inches and 0.392 inches

Fastener Length:

Between 0.612 inches and 0.652 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.428 inches and 0.440 inches

Shoulder Diameter:

0.246 inches first shoulder and 0.249 inches first shoulder

Shoulder Length:

0.260 inches first shoulder and 0.270 inches first shoulder

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-s-416, type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1297 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.