

View Online at <https://aerobasegroup.com/nsn/5306-00-998-5191>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.100 inches and 1.150 inches

**Fastener Length:**

Between 3.360 inches and 3.390 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.673 inches

**Width Between Flats:**

Between 0.803 inches and 0.814 inches

**Extended Washer Diameter:**

Between 1.185 inches and 1.195 inches

**Extended Washer Thickness:**

0.125 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Single Shear Strength:**

132000 pounds per square inch

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 2.240 inches and 2.260 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0