NSN 5306-00-999-5768

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-999-5768



3aThread Direction:Right-handThread Length:Between 0.374 inches and 0.453 inchesFastener Length:Between 0.640 inches and 0.687 inchesHead Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:11Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Right-handThread Length:Between 0.374 inches and 0.453 inchesFastener Length:Between 0.640 inches and 0.687 inchesHead Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Thread Length:Between 0.374 inches and 0.453 inchesFastener Length:Between 0.640 inches and 0.687 inchesHead Style:Head Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Between 0.374 inches and 0.453 inchesFastener Length:Between 0.640 inches and 0.687 inchesHead Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Fastener Length:Between 0.640 inches and 0.687 inchesHead Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Between 0.640 inches and 0.687 inchesHead Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Head Style:HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
HexagonHead Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Head Height:Between 0.109 inches and 0.141 inchesWidth Between Flats:Between 0.365 inches and 0.377 inchesHole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.051 inches Thread Diameter: 0.190 inches Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.051 inches Thread Diameter: 0.190 inches Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Between 0.365 inches and 0.377 inches Hole Diameter: 0.051 inches Thread Diameter: 0.190 inches Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Diameter:0.051 inchesThread Diameter:0.190 inchesGrip Length:Between 0.234 inches and 0.266 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
0.051 inches Thread Diameter: 0.190 inches Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Thread Diameter: 0.190 inches Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
0.190 inches Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Grip Length: Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Between 0.234 inches and 0.266 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
1Hole Type:DrilledFeatures Provided:Finished headThready Qty Per Inch (tpi):32Hole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Finished head Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Thready Qty Per Inch (tpi): 32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
32 Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hexagon flats Material: Iron alloy 660
Material: Iron alloy 660
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5306-00-999-5768 Machine Bolt - Page 2 of 2

Fiig: A003b0

