NSN 5306-01-004-9472

Machine Bolt - Page 1 of 2

Between 0.381 inches and 0.431 inches

Between 0.481 inches and 0.501 inches

Thread Direction:

Thread Length:

Fastener Length:

Right-hand



View Online at https://aerobasegroup.com/nsn/5306-01-004-9472

Head Style:			
Double hexagon w/hole	Э		
Head Height:			
0.260 inches			
Width Between Flats:			
Between 0.243 inches	and 0.251 inches		
Extended Washer Dia	meter:		
0.375 inches			
Extended Washer Thi	ckness:		
Between 0.040 inches	and 0.050 inches		
Hole Diameter:			
0.042 inches			
Thread Diameter:			
0.190 inches			
Grip Length:			
Between 0.070 inches	and 0.100 inches		
Hole Quantity:			
4			
Hole Type:			
Drilled			
Features Provided:			
Finished head			
Nonstandard Thread	Pitch Diameter:		
+0.1644/+0.1667 inche	es		
Thready Qty Per Inch	(tpi):		
32			
Hardness Rating:			
32.0 rockwell c and 30	6.0 rockwell c		
Hole Configuration St	yle:		
Double hexagon longite	udinal hole		
Surface Finish:			
63.0 microinches grip			
Material:			
Steel comp 601			
Material Specification	:		
Ams 6304 assn standa	rd single material response	<u> </u>	

NSN 5306-01-004-9472Machine Bolt - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Nickel or nickel
Surface Treatment Specification:
+16te3e cl a fscm 92215 mfr ref 1st treatment response or ms 2403 assn standard 2nd treatment response
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No.