

View Online at <https://aerobasegroup.com/nsn/5306-01-004-9472>

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.431 inches

Fastener Length:

Between 0.481 inches and 0.501 inches

Head Style:

Double hexagon w/hole

Head Height:

0.260 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

0.375 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

Hole Diameter:

0.042 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.070 inches and 0.100 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Nonstandard Thread Pitch Diameter:

+0.1644/+0.1667 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel or nickel

Surface Treatment Specification:

+16te3e cl a fscm 92215 mfr ref 1st treatment response or ms 2403 assn standard 2nd treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0