

View Online at <https://aerobasegroup.com/nsn/5306-01-006-9462>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.340 inches and 0.507 inches

**Fastener Length:**

Between 1.950 inches and 1.997 inches

**Head Style:**

Double hexagon

**Head Height:**

0.257 inches

**Width Between Flats:**

Between 0.678 inches and 0.689 inches

**Grip Diameter:**

Between 0.4358 inches and 0.4367 inches

**Shank Unthreaded Hole Diameter:**

0.105 inches first hole

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.825 inches first hole and 1.857 inches first hole

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0