

View Online at <https://aerobasegroup.com/nsn/5306-01-007-0851>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.454 inches

**Fastener Length:**

Between 4.564 inches and 4.594 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 4.115 inches and 4.135 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.371 inches first hole and 4.421 inches first hole

**Material:**

Steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0