## NSN 5306-01-007-1525

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-007-1525 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.741 inches **Fastener Length:** 6.010 inches **Head Style:** Round w/wrench flats **Head Diameter:** 1.750 inches **Head Height:** 0.160 inches Width Between Flats: Between 1.483 inches and 1.502 inches **Shoulder Diameter:** Between 1.2475 inches and 1.2490 inches **Shoulder Length:** 4.440 inches **Counterbore Diameter:** Between 0.812 inches and 0.814 inches **Counterbore Depth:** 0.800 inches **Concentric Hole Diameter:** Between 0.312 inches and 0.313 inches **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 270000 pounds per square inch **Special Features:** Second counterbore 0.500 in. Diameter 4.600 in deep from top of head Material:

Steel

### **Material Specification:**

Ams 6419 assn standard single material response

### **Surface Treatment:**

Cadmium head

### **Surface Treatment Specification:**

Qq-c-320 federal specification single treatment response grip

# NSN 5306-01-007-1525

Internally Relieved Body Bolt - Page 2 of 2



Style Designator:
Counterbore unthreaded
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.