

View Online at <https://aerobasegroup.com/nsn/5306-01-007-7054>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.440 inches and 0.507 inches

Fastener Length:

Between 4.825 inches and 4.872 inches

Head Style:

Double hexagon

Head Height:

0.257 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

Between 4.365 inches and 4.385 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.700 inches first hole and 4.732 inches first hole

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0