NSN 5306-01-007-7060

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-007-7060 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.569 inches and 0.619 inches **Fastener Length:** Between 4.204 inches and 4.234 inches **Head Style:** Hexagon **Head Height:** Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.438 inches **Grip Length:** Between 3.615 inches and 3.635 inches Thready Qty Per Inch (tpi): 20 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.993 inches first hole and 4.043 inches first hole **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas677 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-007-7060

Close Tolerance Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0