

View Online at <https://aerobasegroup.com/nsn/5306-01-009-5121>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.250 inches and 0.310 inches

**Fastener Length:**

Between 0.730 inches and 0.780 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.180 inches and 0.200 inches

**Width Between Flats:**

Between 0.600 inches and 0.620 inches

**Hole Diameter:**

0.070 inches

**First Diameter From Head:**

Between 0.496 inches and 0.498 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.050 inches and 0.070 inches

**Thread Diameter:**

0.438 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hole Configuration Style:**

Hexagon longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel

**Material Specification:**

C50t35, general electric co mfr ref single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0