

View Online at <https://aerobasegroup.com/nsn/5306-01-009-6369>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.850 inches and 0.910 inches

Fastener Length:

Between 3.570 inches and 3.590 inches

Head Style:

Hexagon

Head Height:

0.562 inches

Width Between Flats:

Between 1.614 inches and 1.627 inches

Shoulder Diameter:

1.123 inches first shoulder and 1.124 inches first shoulder

Shoulder Length:

3.570 inches first shoulder and 3.590 inches first shoulder

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.210 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0