NSN 5306-01-009-7107

Machine Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** Between 0.620 inches and 0.700 inches Fastener Length: Between 1.365 inches and 1.385 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.685 inches and 0.745 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-009-7107

Machine Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

