NSN 5306-01-010-2290

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-010-2290 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.366 inches and 0.448 inches **Fastener Length:** Between 0.428 inches and 0.448 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Hole Diameter:** 0.047 inches **Thread Diameter:** 0.190 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 **Hole Configuration Style:** Double hexagon flats **Surface Finish:** 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** C50tf13 cl b cagec 07482 mfr ref single material response **Precious Material And Location:** silver

Precious Material:

Silver

NSN 5306-01-010-2290

Machine Bolt - Page 2 of 2

A003b0



| Surface Treatment: |
|--|
| Silver |
| Surface Treatment Specification: |
| Ams 2410 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |