NSN 5306-01-010-2346

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-010-2346
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.535 inches and 0.585 inches
Fastener Length:
Between 1.607 inches and 1.637 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
0.091 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response and mil-c-8837 type 2 cl 2 military specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

26512-gb511w6 manufacturers standard

NSN 5306-01-010-2346

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: