

View Online at <https://aerobasegroup.com/nsn/5306-01-010-2372>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.236 inches and 0.318 inches

**Fastener Length:**

Between 1.372 inches and 1.392 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.095 inches and 0.110 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1894 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.000 inches and 1.016 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.279 inches first hole and 1.309 inches first hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

Retaining element in shank

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 304l

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.