NSN 5306-01-010-9939

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-010-9939

Thread Length: Between 0.475 inches and 0.525 inches **Fastener Length:** Between 2.860 inches and 2.890 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 2.365 inches and 2.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-01-010-9939

Shear Bolt - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.