## NSN 5306-01-011-4037

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-011-4037

<b>-</b>
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.443 inches and 0.493 inches
Fastener Length:
Between 0.765 inches and 0.795 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
Between 0.059 inches and 0.079 inches
Hole Diameter:
0.037 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Hexagon flats
Material:

Surface Treatment:

Steel comp xm-13

**Material Specification:** 

Ams 5629 assn standard single material response

Passivate

## NSN 5306-01-011-4037

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0