NSN 5306-01-012-0623



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-012-0623 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.565 inches and 0.615 inches **Fastener Length:** Between 1.450 inches and 1.480 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.338 inches and 0.358 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Grip Diameter:** Between 0.311 inches and 0.312 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Stsbs002 cagec 98897 mfr ref single material response **Surface Treatment:** Nickel and cadmium and chromate **Surface Treatment Specification:** Stsbs002 cagec 98897 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-012-0623

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0