NSN 5306-01-012-0624



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-012-0624 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.707 inches and 0.757 inches **Fastener Length:** Between 2.592 inches and 2.622 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.300 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** Between 0.059 inches and 0.079 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response **Surface Treatment:**

Nickel and cadmium and chromate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-012-0624

Shear Bolt - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0