

View Online at <https://aerobasegroup.com/nsn/5306-01-013-5726>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.440 inches and 0.507 inches

**Fastener Length:**

Between 2.075 inches and 2.122 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.247 inches and 0.267 inches

**Width Between Flats:**

Between 0.678 inches and 0.689 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.615 inches and 1.635 inches

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.947 inches first hole and 2.004 inches first hole

**Material:**

Steel

**Material Specification:**

23-105, fscm 76301 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mac ps13145, mcdonnell douglas corporation mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

08524-b-17028 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0