

View Online at <https://aerobasegroup.com/nsn/5306-01-013-5726>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.440 inches and 0.507 inches

Fastener Length:

Between 2.075 inches and 2.122 inches

Head Style:

Double hexagon

Head Height:

Between 0.247 inches and 0.267 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

20

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.947 inches first hole and 2.004 inches first hole

Material:

Steel

Material Specification:

23-105, fscm 76301 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mac ps13145, mcdonnell douglas corporation mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

08524-b-17028 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0