

View Online at <https://aerobasegroup.com/nsn/5306-01-013-8939>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.482 inches

Head Style:

Hexagon

Head Height:

Between 0.296 inches and 0.328 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.145 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 1.973 inches and 1.978 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.353 inches first hole

Material:

Steel comp 4130

Material Specification:

Mil-s-5000 cond d military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.