NSN 5306-01-013-9429

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-013-9429

View Online at https://aerobasegroup.com/nsn/5306-01-013-9429
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.585 inches and 0.635 inches
Fastener Length:
Between 4.033 inches and 4.063 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.309 inches and 0.329 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.040 inches and 0.060 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 3.428 inches and 3.448 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837 type 2 cl 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-013-9429

Shear Bolt - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.