NSN 5306-01-013-9430

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-013-9430

View Online at https://aerobasegroup.com/nsn/5306-01-013-9430					
Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.586 inches and 0.636 inches					
Fastener Length:					
Between 4.158 inches and 4.188 inches					
Head Style:					
Double hexagon w/hole					
Head Height:					
Between 0.309 inches and 0.329 inches					
Width Between Flats:					
Between 0.367 inches and 0.376 inches					
Extended Washer Diameter:					
Between 0.575 inches and 0.585 inches					
Extended Washer Thickness:					
Between 0.040 inches and 0.060 inches					
Grip Diameter:					
Between 0.3110 inches and 0.3120 inches					
Thread Diameter:					
0.312 inches					
Grip Length:					
Between 3.552 inches and 3.572 inches					
Thready Qty Per Inch (tpi):					
24					
Min. Tensile Strength (psi):					
260000 pounds per square inch					
Hardness Rating:					
51.0 rockwell c and 54.0 rockwell c					
Material:					
Steel comp h11					
Material Specification:					
Ams 6485 assn standard single material response or ams 6487 assn standard single material response					
Surface Treatment:					
Cadmium					
Surface Treatment Specification:					
Mil-c-8837 type 1 cl 2 military specification single treatment response					
Thread Series Designator:					
Unjf					
Shelf Life:					
N/a					

NSN 5306-01-013-9430

Shear Bolt - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.