## NSN 5306-01-013-9564

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-013-9564 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.745 inches **Fastener Length:** Between 2.042 inches and 2.072 inches **Head Style:** Hexagon **Head Height:** Between 0.234 inches and 0.266 inches Width Between Flats: Between 0.679 inches and 0.689 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.297 inches and 1.327 inches **Features Provided:** Casehardened and finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 or steel comp 630 **Material Specification:** Ams 5733 assn standard 1st material response or ams 5735 assn standard 2nd material response or ams 5737 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas1007 professional/industrial association standard Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5306-01-013-9564

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.