

View Online at <https://aerobasegroup.com/nsn/5306-01-014-0704>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.754 inches and 0.774 inches

**Fastener Length:**

Between 1.940 inches and 1.950 inches

**Head Style:**

Dee chamfer

**Head Diameter:**

0.664 inches

**Head Height:**

Between 0.165 inches and 0.175 inches

**Distance From Centerline To Flat:**

0.332 inches

**First Diameter From Head:**

Between 0.3754 inches and 0.3756 inches

**Second Diameter From Head:**

Between 0.3350 inches and 0.3450 inches

**Third Diameter From Head:**

Between 0.3754 inches and 0.3756 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.260 inches and 0.270 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.860 inches and 0.870 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 1.176 inches and 1.186 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Nickel

**Material Specification:**

C50tf13 cl a fscm 07482 mfr ref single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0