NSN 5306-01-014-1191

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-014-1191

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.843 inches and 0.893 inches **Fastener Length:** Between 4.165 inches and 4.195 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.608 inches and 0.628 inches Width Between Flats: Between 0.679 inches and 0.690 inches **Extended Washer Diameter:** Between 1.040 inches and 1.050 inches **Extended Washer Thickness:** Between 0.140 inches and 0.160 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 3.302 inches and 3.322 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf

Specification Data:

56878-lwb22 manufacturers standard

NSN 5306-01-014-1191

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0